

**Incomagri**

TANK TRAILER  
**CTIN**



# TANK TRAILER

## CTIN

The CTIN Incomagri trailed tank with lobular pump is an essential machine in agricultural and livestock farm. It can be used in various applications, as firefighting, water transportation for small irrigations, sprayers supply, collection and distribution of pig slurry, Stable and machinery washing.



- /// Incomagri® lobe pump of 3' and 4', suction and distribution of liquids.
- /// BI-3": 900l/min.
- /// BI-4": 1200l/min
- /// Internal epoxy-based anticorrosion coating
- /// Rear cover with full opening

- /// 140mm top cap for gravity supply
- /// Break waves in tanks from 5000l
- /// Fire kit (optional)
- /// Tires: Single, double or tandem, 16", 20" or 15.5" (high fluctuation) rings \* vary by capacity.

TECHNICAL SPECIFICATIONS						
Model	2000	3000	4000	5000	6000	8000
Weight	880	1100	1453	1665	2250	2250
Lenght (mm)	4,10	4,85	4,97	5,10	6,30	6,30
Height (mm)	3,0	3,0	3,56	3,30	3,45	3,45
Width (mm)	1,68	1,68	2,05	1,80	2,15	2,15
Tractor power required (hp)	45	65	75	75	100	100
Loading time	BI-3"- 3'30/ BI-4 - 3"	BI-3"- 4'40/ BI-4 - 3'30"	BI-3"- 4'40"/ BI-4 - 5'	BI-3"-7'/ BI-4 - 5'	BI-3"-10/ BI-4 - 8'	BI-3"-10/ BI-4 - 8'
Unloading time	BI-3"-3'30 BI-4 - 2'30"	BI-3"-5' BI-4 - 3'30"	BI-3"-5'/ BI-4 - 4'40"	BI-3"-7'/ BI-4 - 4'40"	BI-3"-10/ BI-4 - 8'	BI-3"-10/ BI-4 - 8'
Tyres for single wheel	10,5 x 65-16	10,5 x 65-16	1000 x 20 rtd	1000 x 20 rtd	1000 x 20 rtd	1000 x 20 rtd
Tyres for double wheel	7,50 x 16	7,50 x 16	1000 x 20 rtd	1000 x 20 rtd	1000 x 20 rtd	1000 x 20 rtd
Distribution range (flat nozzle)	14 a 17	14 a 17	14 a 17	14 a 17	14 a 17	14 a 17

(\*) for height without kit remove 1500 mm, for tank weight without kit remove 88 kg.

\*Weight and dimensions may vary depending on the product version.  
Project changes may occur without prior notice.

*\*Merely illustrative images*



Rod. Estadual SP-147, 41 - 13.974-905 - Itapira/SP  
incomagri@incomagri.com.br

**(19) 3843-9900**

